



### GENERAL NOTES

1. THE LANDSCAPE AREA BETWEEN THE SIDEWALK AND BACK OF CURB SHALL BE DEPRESSED AND COVERED IN ROCK TO PREVENT EROSION.
2. CHECK DAMS ARE REQUIRED FOR SWALES ON LONGITUDINAL SLOPES 4.0% AND GREATER. THE ENGINEER WILL DETERMINE THE LOCATION.

### CONSTRUCTION NOTES

- A. FOR LANDSCAPE BUFFERS GREATER THAN 10 FEET WIDE THE MAXIMUM DEPTH SHALL BE 10 INCHES.
- B. 2% PROJECTED SLOPE FROM BACK OF CURB TO EDGE OF SIDEWALK.
- C. SURFACE BETWEEN BACK OF CURB AND SIDEWALK SHALL BE COVERED WITH ANGULAR GRAVEL MULCH (MINIMUM SIZE  $\frac{3}{4}$ " ), COBBLES, OR RIPRAP. THICKNESS TO BE "D<sub>50</sub> X 1.5" WITH A MINIMUM OF 2".
- D. FILTER FABRIC PER SECTION 603 OF THE SPECS.
- E. CURB AND GUTTER PER PLAN.
- F. SIDEWALK. PER PLAN.
- G. MIN 12" COMPACTED SUBGRADE.
- H. COMPACT SUBGRADE 12" BEHIND CURB.
- I. ANGULAR GRAVEL MULCH TO BE GRAY OR BROWN COLORED AND MATCH COLOR OF ADJACENT AGGREGATE.

|           |                        |
|-----------|------------------------|
| REVISIONS | CITY OF ALBUQUERQUE    |
| 12/2022   | PAVING                 |
|           | LANDSCAPE BUFFER SWALE |
|           | DWG. 2414              |
|           | DECEMBER 2022          |